

Extraction Arms

Extraction Arms

Flanged Hood



Extraction arm with flanged hood

Application Range

- » Extraction of individual and multiple workstations in industrial and skilled trade applications
- » For connection to extraction unit or pipework




Ideal for

- Fumes
- Vapors
- Dusts
- Shavings



Extraction arm at a welding station

Mounting Possibilities



- A Wall-mount console (standard model)
- B Standpipe (for positioning in a suitable holding device at a machine or at the extraction equipment)
- C Floor standpipe, height: 1.000 mm, for extraction arm with standpipe

ESTA PLUS

Special Features

- » External beam construction
- » Unobstructed air flow inside the extraction arm
- » Gas springs for easy adjustment
- » Optional: reducer and gate valves available for regulating the airflow
- » Optional: installation of lighting
- » Optional: ATEX version

Your Benefits

- » Large selection of diameters and sizes
- » High flexibility
- » Easy handling
- » Targeted extraction

Technical Data

Extraction arms with flanged hood										
	Ø 50	Ø 70	Ø 80	Ø 100	Ø 125	Ø 140	Ø 150	Ø 160	Ø 180	Ø 200
Length / Order Number										
1.500 mm	50.152	70.152	80.152	10.152	12.152	14.152	15.152	16.152	18.152	–
2.000 mm	50.202	70.202	80.202	10.202	12.202	14.202	15.202	16.202	18.202	20.202
3.000 mm	50.302	70.302	80.302	10.302	12.302	14.302	15.302	16.302	18.302	20.302
4.000 mm	–	–	–	10.4024	12.4024	14.4024	15.4024	16.4024	–	–
4.000 mm ¹⁾	–	–	–	10.402	12.402	14.402	15.402	16.402	18.402	20.402
5.000 mm ¹⁾	–	–	–	10.502	12.502	14.502	15.502	16.502	18.502	20.502
6.000 mm ²⁾	–	–	–	10.602	12.602	14.602	15.602	16.602	18.602	20.602
8.000 mm ³⁾	–	–	–	10.8024	12.8024	14.8024	15.8024	16.8024	–	–

¹⁾inkl. 2.0m extension boom / ²⁾inkl. 3.0m extension boom / ³⁾inkl. 4.0m extension boom