

# E-Hand DTX 2500 (MMA)

## The reliable support at the construction site

- Easy handling
- Stable arc for optimal welding results
- Low weight
- Extremely reliable



Type		DTX 2500 (MMA)
Main voltage (± 15 %)		3 x 400 V / 50–60 Hz
Actual power output max		10,4 kVA
Welding current		5–250 A
No-load voltage		85 V
Welding voltage		20,2–30 V
Welding current / Duty cycle	35%	250 A (10 min / 40°C)
	100%	170 A (10 min / 40°C)
Safety class / Cooling system		IP 23S / F
Switching steps		infinitely
Dimensions L x B x H		480 x 225 x 480 mm
Weight		24 kg

Art. No.	Description
0004-04-0011	DTX 2500 MMA welding power source gascooled
0050-04-0021	Welding cable, 35 mm <sup>2</sup> , 200 A, 5 m (with plug)
0050-04-0003	Earth cable, 4 m, 50 mm <sup>2</sup> , 400 A, with clamp and DIX plug

Art. No.	Description
Welding accessories	
0250-99-0012-10,5	OTC MIG/MAG welding glove, full/split leather
0220-99-0001	Special MIG universal pliers, blue
0223-99-0002	Chipping hammer, 360 g, straight PVC handle, red
0221-99-0001	Wire brush
0222-99-0001	Hand shield PVC, black
0224-99-0002	Clear glass
0224-99-0001	Protective glass, class 9
0226-99-0001	OTC Vision (automatic welding helmet, protection levels 4/9–13)